

ISEKI TH Series SPECIFICATIONS

TH4365

MODEL

Drive 4WD

ENGINE SPECIFICATION

Engine Iseki E3CG
No. Cylinders / cc 3 / 1647
Engine Power kW/hp 27/36
@ rated speed 2600
Speed control manual pedal & cruise control

PTO

PTO kW / hp 21 / 28
Type Independent
Speeds Rear 540 / 1000
Mid PTO 2000@2500
Configuration rear/mid 6 spline / 15 spline

TRANSMISSION

Type Hydrostatic
Speeds Fwd/Rev 3 / 3
Speed Range Std/Max F: 0 - 28.6 R: 0 - 21.7

HYDRAULIC SYSTEM

Description Open Centre
Pump Type Gear
Max l/min (Main pump) 32
Remote Outlets Std/Max 2F 0R / 2F 2R

3 POINT LINKAGE

Type Cat I
Control Position
Lift - kg@610mm 730
Lift - kg@BE 1100

BRAKES & STEERING

Brake Type Wet disc
Steering Type Hydrostatic

AXLE CAPACITY

Rear Axle 1100kg
Front Axle 900kg

TYRE EQUIPMENT - AG

Standard Front 6.00 - 14
Standard Rear 12.4 - 16

DIMENSION/WEIGHTS

Minimum Width 1430mm
Height 2455mm
Wheel base 1695mm
Ground Clearance 220mm
Dry Shipping Weight 1220kg

CAPACITIES

Fuel 35 litres
Transmission 34 litres
Engine crankcase 5.4 litres



ISEKI



FREECALL: 1800 802 914
www.agco.com.au



smart, reliable created with you in mind
www.iseki.com.au

TH Range Compact Tractors All torque. All Action.

36hp

Specifications, standard and optional equipment on products change from time to time. Please consult your local dealer to ensure your expectations are matched by the product which will be available locally at the time you take delivery.

ISEKI TH RANGE FEATURES



POWERFUL ENGINE

Now boasting a bigger 36hp Iseki engine, delivering plenty of power at a low 2600rpm. Efficient and powerful. What you expect from an Iseki engine.



ERGONOMIC OPERATOR AREA

An iso mounted platform reduces noise and vibration. A Deluxe seat is standard and controls are located on the fenders for more room and better control.




IMPLEMENT CONTROL

Large linkage and hydraulic capacity, a 540/1000 PTO and extendable drawbar is suitable to a large range of implements.



HYDROSTATIC TRANSMISSION

Three range hydrostatic transmission give you more options and more working ranges. • Easy to use side by side forward and reverse pedals make directional changes smooth. • 4 wheel drive and differential lock for exceptional traction in all conditions.



NEW DESIGN

Rounded bonnet gives a modern look and has improved visibility for front-end loader application.



SERVICEABILITY

Easy access to the whole engine and daily check points easy to reach.



PTO

The independent PTO with 2 speed modulation control for slow and smooth engagement. 540 and 1000 speed rear and a mid PTO as standard.



VERSATILE

AG or Turf tyres, Front end loader or 60 inch mower, the Iseki TH4365 is designed to take on a multitude of tasks.



THE NEXT GENERATION

Iseki's determination to strive for perfection in the compact tractor sector is reflected in the next generation TH Series. The impressive new tractor range boasts more power and better features befitting the most astute owner who demands nothing short of top performance, comfort and value in a compact tractor.

Clever, sleek new design and smart engineering combine with proven features to produce the new benchmark in compact tractors – the TH4365.

Whether it's a high performing professional mower to tackle the big jobs or a premium compact tractor, you can count on Iseki to deliver time and time again.

Formed in 1926, Iseki has been designing, manufacturing and supplying tractors worldwide for over 80 years and with over 30 years experience in the Australian market, Iseki is the brand you can trust.



Built to impress. The Iseki difference.