

ISEKI TM Series SPECIFICATIONS



TM 3200 R.O.P.S

| Model | TM3245 | TM3265 |
|----------------------|-------------------------------|-----------|
| Drive | 4WD | 4WD |
| Engine Specification | | |
| Engine | E3112-B33 | E3CD-B70 |
| Number Cylinders/cc | 3/1123 | 3/1498 |
| Engine Power kW/hp | 16.8/22.5 | 18.9/25.7 |
| @ Rated speed | 2600 | 2600 |
| Speed control | Manual pedal & cruise control | |
| PTO | | |
| PTO kW/hp | 12.9/17.3 | 15/20.1 |
| Type | Independent | |
| Speeds Rear/Mid | 540/2000 | |
| Transmission | | |
| Type | Hydrostatic | |
| Speeds Fwd/Rev | 3 / 3 | |
| Speed Range | F: 0-24.4 R:0-16.6 | |

| Model | TM3245 | TM3265 |
|------------------------|-------------|--------|
| Hydraulic System | | |
| Description | Open centre | |
| Pump Type | Gear | |
| Max l/min | 33 | |
| Remote outlets Std/max | 2/2 | |
| 3 Point Linkage | | |
| Type | Cat 1 | |
| Control | Position | |
| Lift – kg @ BE | 600 | |
| Brakes and Steering | | |
| Brake type | Wet disc | |
| Steering type | Hydrostatic | |

| Model | TM3245 | TM3265 |
|-----------------------|------------|--------|
| Tyre Equipment | | |
| Standard Front (AG) | 6.0-12 | |
| Standard Rear (AG) | 9.5-18 | |
| Standard Front (TURF) | 23x10.5-12 | |
| Standard Rear (TURF) | 315/75D15 | |
| Dimension/Weights | | |
| Minimum Width | 1100 | |
| Height | 2420 | |
| Wheelbase | 1560 | |
| Dry Shipping Weight | 825 | 845 |
| Capacities | | |
| Fuel | 27 | |



Specifications, standard and optional equipment on products change from time to time. Please consult your local dealer to ensure your expectations are matched by the product which will be available locally at the time you take delivery.



www.iseki.com.au

TM Range Compact Tractors All torque. All Action.

23 & 26hp

ISEKI TM RANGE TRACTORS

The ultimate compact tractor, that was the goal at Iseki when we set out to redesign the TM Series. You'll feel the difference right from the moment you get behind the wheel.

Everything is in its right place – the controls have been moved up onto the fenders for easier access, so there is no more reaching for levers and controls. The Independent PTO button is smartly positioned in front of the operator and now features a two-speed modulation button for slower engagement, further adding to operator convenience.

The repositioning for the controls has allowed for a bigger and improved spring suspension seat and combined with the Iso-mounted platform provides an even smoother and comfortable ride.

The new range now also features the 26hp TM3265 model providing the option of extra power if required.

Iseki's TM Series, feel the difference today!



THE ISEKI DIFFERENCE

When you choose Iseki, you're not simply buying a tractor, you're investing in 80 years of industry-leading engineering and manufacturing experience. Experience that continues to produce high quality and top performing products that are built to meet today's ever increasing demands.


While Iseki has made its mark internationally, you can still feel confident knowing that they understand the unique industries of each country. With over 25 years in the Australian market they have built solid and reliable foundations, continuously delivering superb products and services that work even harder for your specific needs.

You get the expertise of your local Iseki dealer who will match the right tractor to your business and even provide flexible finance options to help fund your purchase.

Combine this with peace of mind from first-class parts and service support and you'll see what we mean by the Iseki Difference.



FEATURES



- ENGINE**
- Powerful Iseki 3 cylinder water-cooled engines.
 - Quiet and efficient.
 - Large displacement offers full power at low engine RPM.
 - Removable side panels allow easy access to the engine, making service and regular maintenance easier.




- HYDROSTATIC TRANSMISSION**
- Three range hydrostatic transmission give you more options and more working ranges.
 - Easy to use side by side forward and reverse pedals make directional changes smooth.
 - 4 wheel drive and differential lock for exceptional traction in all conditions.



- INDEPENDENT PTO**
- Independent 540 rear PTO and 2000 mid PTO for quick and easy operation by the flick of a switch.
 - The PTO can be engaged or disengaged at any time even on the move.
 - A Two speed modulation control button for slower PTO engagement.



- OPERATORS PLATFORM**
- Large operator's platform sit on rubber mounts isolating the operator from the chassis reducing vibration and operator fatigue.
 - Operator controls are mounted on both fenders putting the operator in control of the tractor and the implements.
 - A large spring suspension seat with adjustable armrests is standard with an increased capacity of 130kg with adjustability to suit each operator.



- HYDRAULICS & LINKAGE**
- 2 rear double acting auxiliary remotes are standard on the TM series. Controls are located conveniently on the right hand fender.
 - With two hydraulic pumps and up to a max 33 l/min flow you fill in control and loader work becomes a breeze.
 - Large three point linkage capacity of 600kg @ ball ends.
 - Clevis drawbar



- OPTIONS**
- Ag and turf tyres option are available.
 - Standard with a mid PTO a 60" mid mount mower deck is easily fitted.
 - 7 stage height adjustment from 25-115mm and a hydraulic deck lift when not in use.
 - Robust front and rear axles, great for front end loaders.